









1a Max. Lift Height 4040mm 1b Freelift Height 0mm 2 Height Mast Closed 2855mm 3 Max. (Mast raised) 4870mm 4 Overall Length 1950mm 2300mm 2500mm 5 Mast Travel 950mm 1300mm 1450mm 6 Ground Clearance Under Mast 150mm 100mm 7 Ground Clearance to Centre of Wheelbase 2440mm 100mm 8 Height Over Cab (Without work lights) 2440mm 2440mm 9 Width 2270mm 2270mm 10 Outside Spread of Fork Arms 1350mm 1350mm 11 Track Front 2025mm 1400mm 12 Frame Opening 1400mm 600mm 600mm 13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 1545mm 1895mm 2045mm 15 Wheelbase 1545mm 1100mm 1150mm 150mm </th
2 Height Mast Closed 2855mm 3 Max. (Mast raised) 4870mm 4 Overall Length 1950mm 2300mm 2500mm 5 Mast Travel 950mm 1300mm 1450mm 6 Ground Clearance Under Mast 150mm 7 Ground Clearance to Centre of Wheelbase 110mm 8 Height Over Cab (Without work lights) 2440mm 9 Width 2270mm 10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 170mm 1100mm 1150mm 45° 19 Ramp Angle 17° 45° 17° 20 Departure Angle 45° 17° 20 17° 17°
3 Max. (Mast raised) 4870mm 4 Overall Length 1950mm 2300mm 2500mm 5 Mast Travel 950mm 1300mm 1450mm 6 Ground Clearance Under Mast 150mm 7 Ground Clearance to Centre of Wheelbase 110mm 8 Height Over Cab (Without work lights) 2440mm 9 Width 2270mm 10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 1150mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt
4 Overall Length 1950mm 2300mm 2500mm 5 Mast Travel 950mm 1300mm 1450mm 6 Ground Clearance Under Mast 150mm 7 Ground Clearance to Centre of Wheelbase 110mm 8 Height Over Cab (Without work lights) 2440mm 9 Width 2270mm 10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 2045mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5°
5 Mast Travel 950mm 1300mm 1450mm 6 Ground Clearance Under Mast 150mm 7 Ground Clearance to Centre of Wheelbase 110mm 8 Height Over Cab (Without work lights) 2440mm 9 Width 2270mm 10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 1100mm 1150mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000
6 Ground Clearance Under Mast 150mm 7 Ground Clearance to Centre of Wheelbase 110mm 8 Height Over Cab (Without work lights) 2440mm 9 Width 2270mm 10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 2045mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 1100mm 1150mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 </td
7 Ground Clearance to Centre of Wheelbase 110mm 8 Height Over Cab (Without work lights) 2440mm 9 Width 2270mm 10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 1100mm 1150mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 45° 19 Ramp Angle 17° 20 20 Departure Angle 45° 3° 21 Forward Tilt 3° 28 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
7Wheelbase110mm8Height Over Cab (Without work lights)2440mm9Width2270mm10Outside Spread of Fork Arms1350mm11Track Front2025mm12Frame Opening1400mm13Load Centre Distance450mm600mm14Overhang Front220mm15Wheelbase1545mm1895mm16Overhang Back135mm17Length From Face of Fork1100mm1100mm1150mm18Approach Angle45°19Ramp Angle17°20Departure Angle45°21Forward Tilt3°22Backward Tilt5°23Minimum Outside Radius2000mm2325mm2490mm24Platform Height485mm
6 (Without work lights) 2440mm 9 Width 2270mm 10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 1545mm 1895mm 2045mm 16 Overhang Back 135mm 135mm 1100mm 1150mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 45° 19 Ramp Angle 17° 20 20 Departure Angle 45° 3° 21 Forward Tilt 3° 24 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
10 Outside Spread of Fork Arms 1350mm 11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 1100mm 1150mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 45° 19 Ramp Angle 17° 45° 20 Departure Angle 45° 45° 21 Forward Tilt 5° 28 22 Backward Tilt 5° 2490mm 24 Platform Height 485mm
11 Track Front 2025mm 12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 1545mm 1895mm 2045mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 1100mm 1100mm 1150mm 18 Approach Angle 45° 17°
12 Frame Opening 1400mm 13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
13 Load Centre Distance 450mm 600mm 600mm 14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
14 Overhang Front 220mm 15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
15 Wheelbase 1545mm 1895mm 2045mm 16 Overhang Back 135mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
16 Overhang Back 135mm 17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
17 Length From Face of Fork 1100mm 1100mm 1150mm 18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
18 Approach Angle 45° 19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
19 Ramp Angle 17° 20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
20 Departure Angle 45° 21 Forward Tilt 3° 22 Backward Tilt 5° 23 Minimum Outside Radius 2000mm 2325mm 2490mm 24 Platform Height 485mm
21Forward Tilt3°22Backward Tilt5°23Minimum Outside Radius2000mm2325mm2490mm24Platform Height485mm
22Backward Tilt5°23Minimum Outside Radius2000mm2325mm2490mm24Platform Height485mm
23Minimum Outside Radius2000mm2325mm2490mm24Platform Height485mm
24 Platform Height 485mm
25 Platform Length 850mm 1200mm 1350mm
A Capacity 3000kg 4000kg 5000kg
B Unladen Weight 6300kg 6650kg 6850kg
C Maximum Ground Speed 10km/h
D Gradeability 10%
E Battery Capacity (V / Ah) 80V / 620Ah
F Fork Section 50mm x 150mm x 1350mm
G 405x305x220 Front Tyre OD 406mm / Width 220mm (Solid Rubber)
H 27 x 10-12 Rear Tyre OD 680mm / Width 255mm
I Standard Colour Green & Grey
J AC Electric Traction Motor x 2 80v / 5kW
K AC Electric Pump Motor 80V / 19kW

International Patent Application No. PCT/EP2014/053066; UK Patent Application No. GB 1302811.3

Features Include:

- Rubber Mounted Cabin
- AC Motor Technology
- Multi-Direction Operation
- Load Sensing Steering
- Curtis AC Software
- 4 Way Lever Positioning of Wheels
- 2 Wheel Drive

Co. Monaghan Ireland +353 47 80500 info@combilift.com

Distributed by:





